

m3c2i centre channel loudspeaker

Carefully timbre matched to the **m3i** series acoustic characteristics, the **m3c2i** centre channel loudspeaker provides excellent clarity and dynamic performance in home cinema installations for screen based dialogue and effects.

The **m3c2i** is fully magnetically shielded to allow the unit to be placed in close proximity to TV and video monitors, and its high sensitivity and easy-drive characteristics make it suitable for all AV amplifiers.

Twin 100mm DiaDrive bass units integrate seamlessly with the Viotex fabric dome treble unit ensuring wide bandwidth and fine detailing. The new i-series crossover takes into account the baffle diffraction effect to give a more open and detailed midrange performance, with superior integration between the drive units for smoother treble output. In addition crossovers are now wired to drive units using Mission's special HP-OFC (High Purity Oxygen Free Copper) cable with its dedicated bass and treble formulations.

features

DiaDrive Bass Unit
Viotex fabric dome Treble Unit
Long hair fibre damping

High quality bass crossover components

High quality treble crossover components
HP-OFC cables

Easy amplifier load
Magnetically shielded

benefits

Reveals the full energy of the music signal
Fine detailing and extended bandwidth at HF
Excellent balance between absorption and damping of internal cabinet energy
Laminated Silicon Iron coils reduce level dependant distortion
Audiophile grade capacitors ensure HF clarity
Improved definition and detailing across the audio band
Suits all types of amplification
Suitable for hi-fi stereo and AV use

construction

Enclosure
Grille
Damping

28mm and 15mm MDF
Acoustically transparent cloth
Acoustic long hair fibre

electrical

L.F. Unit
H.F. Unit
Crossover
Terminals

Twin 100mm DiaDrive
25mm Viotex soft dome with FF cooling
Acoustic 2nd order
Gold plated, Multi-way binding posts

specifications

Enclosure type	2-way reflex loaded
In-room Frequency Bandwidth	-6dB at 52Hz and 28kHz
Frequency response ± 3 dB	56Hz – 20 kHz
Nominal Impedance	8 Ohms compatible (min. 4.2 $\square$)
Sensitivity SPL/m/2.83v	91dB
Recommended amplifier power	25 - 125W
Crossover frequency	2.8 kHz
Effective volume	9.7 litres
Cabinet dimensions (HxWxD)	165 x 430 x 230 (mm), 6.5 x 16.9 x 9.1 (inches)
Weight	6.7 Kg, 14.8 lbs. (per speaker cabinet)
Finish	Graphite Black, Beech, Cherry or Satin Silver

setting up

- RUN IN for at least 24 hours before serious listening.
- Place on or under a TV monitor or wall mount near a screen.
- May be used with any competent budget electronics.
Will clearly show improvements as source improves.