

volare v63 loudspeaker



The tall, elegant EISA award winning **v63** features twin 150mm Paramid drivers flanking a 25mm microfibre dome treble unit, delivering maximum impact and excitement to both music and movies. Highly efficient, the **v63** makes the most of your audio equipment with an amplifier suitability of 25-150 watts per channel.

Bass extension deep enough to satisfy organ enthusiasts and fine treble detail beyond the limit of human hearing only tell part of the **v63** story. The real benefits are a lucid and informative character at any frequency, a loudspeaker that reveals the true scale of the wide bandwidth and dynamic range of modern sound formats.

features

Smoothly contoured cabinet
38mm machined MDF front baffle
4th Generation TFCT enclosure

Twin 150mm Paramid bass drivers

32mm bass voice coil
Advanced microfibre treble unit
Laser trimmed pressure balanced dome
Audiophile grade crossover

Anti-turbulence rear mounted port
Magnetically shielded
IDG (Inverted Driver Geometry)

benefits

Excellent dispersion for a wide listening angle
High rigidity support for maximum transient impact
Transverse Folded Cabinet Technology for optimum rigidity and control of resonance
Sandwich of Aramid and pulp fibres for lucid midrange and optimum bass energy
High power handling and efficiency
Excellent treble detail at all listening levels
Improves treble dynamics and transient accuracy
Silicon iron Inductors and Polypropylene capacitors in the signal path for ultimate signal clarity and detail resolution
Clean, tight bass without midrange smear
Suitable for hi-fi stereo and AV use
Smooth phase response through the crossover region helps precision stereo imaging

construction

Enclosure
Grille
Damping

38mm and 25mm MDF with real wood veneers
Acoustically transparent polyester weave
Acufil long fibre

electrical

L.F. Unit
H.F. Unit

Crossover
Terminals

Twin 150mm Paramid drivers with 32mm voice coils
25mm microfibre dome with neodymium magnet and ferrofluid cooling
Acoustic second order
Gold plated, bi-wireable multi-way binding posts

specifications

Enclosure type	2-way reflex loaded
Frequency response ± 3 dB	44Hz – 20kHz
Nominal Impedance	8 Ohms compatible (min. 5 Ω)
Sensitivity SPL/m/2.83v	89dB
Recommended amplifier power	25-150W
Crossover frequency	2.4kHz
Effective volume	30 litres
Cabinet dimensions (HxWxD)	968 x 205 x 330 (mm), 38.1 x 8.1 x 13 (inches)
Weight	23 Kg, 50.6 lbs. (per speaker cabinet)
Finish	Black ash, Beech or Cherry real wood veneers

setting up

- RUN IN for at least 24 hours before serious listening.
- Use supplied floor standing spikes for optimum performance
- Position within 20cm – 80cm of rear wall.
- Use good quality speaker cables.

Note: The recommended amplifier power rating is for undistorted power. Loudspeakers will be damaged by amplifiers overdriven into distortion, no matter what the power rating of the amplifier. For larger rooms or high listening levels it is safer to choose an amplifier with a power output near the maximum rating of the loudspeaker.

