

Dear VPI customer,

Thank you for joining the VPI family with your purchase of the Cliffwood Phono Preamplifier. This easy startup guide will give you the Cliffwood specs and information to start enjoying your music!

Thank You!

Mat Weisfeld

VPI President



### Cliffwood Phono Spec:

Low-noise op-amp design, regulated linear power supply

- Gain 44db
- Input loading: 47K Ohm -180pF
- Maximum input level: 125mV
- Input sensitivity: 3mV for 500mV output
- Frequency response (50K Ohm load):17Hz (-3dB) to 75KHz (-0.2dB)
- RIAA accuracy (50K Ohm load): +/-0.18dB 100Hz to 75KHz
- Power requirements: 110VAC @ 100mA

The Cliffwood phono is meant to be a compliment to the VPI Cliffwood turntable as well as other VPI branded products. The main concept is for you to have an easier start with your listening experience.

### Warning

- Do not expose the equipment to water, rain, or excessive moisture.
- Do not handle the main leads with wet hands.
- Do not expose to an open flame.
- As much as you might want to, do not take a bath with your Cliffwood Phono Preamplifier

### Getting Started

After safely removing the Cliffwood from the box, plug in the Cliffwood Phono Preamplifier from the back into the wall (or other power alternative) and press the power button to turn it on. You will know the Cliffwood is turned on when the blue LED light on the front is lit.



## Plugging in the RCA Connectors

You can use any standard or off the shelf high-end RCA cable to connect to your Cliffwood Phono. Make sure to connect the RCA from your turntable into the "Input" labeled connection. Make sure to connect your RCA cable connecting to your amplifier in the "Output" labeled connection.



Please remember the Cliffwood Phono is a Moving Magnet phono and will not perform optimally with Moving Coil. Feel free to contact your VPI Dealer, or VPI directly with any questions or concerns.

### **VPI Industries, Inc. Limited Warranty**

VPI Industries, Inc. (VPI) warrants this unit against defects in materials and/or workmanship for one (1) year from the date of purchase by the original retail purchaser. VPI's sole obligation under this warranty is limited to the repair or replacement, at VPI's option, of any part(s) found to be defective. VPI's obligation to repair or replace defective parts is the purchaser's sole and exclusive remedy, and VPI shall not be liable for any direct or indirect injury and/or property damage arising out of the use of the product or defect in or failure of the product.

This warranty does not extend to any unit whose serial number has been defaced or altered. Any product that VPI determines causes a defect or malfunction due to incorrect installation, modification, misuse, or servicing by the purchaser, or service technician not authorized by VPI to perform such service will not be warranted. This warranty does not cover trivial or cosmetic defects that do not impair the unit's normal function.

VPI reserves the right to make changes in this product without assuming any obligation to install such change in any product previously manufactured. This warranty to repair or replace defective parts is in lieu of all other express or implied warranties of merchantability or fitness for a particular purpose. There are not warranties that extend beyond the description herein.

Some states do not allow exclusion of implied warranties or limitation of incidental or consequential damages, so the above exclusion or limitations may not apply to you. This warranty gives you specific legal rights, and you may also have other rights that vary from state to state.

Register your Product Online:

<http://vpiindustries.com/warranty/>

